

TECHNICAL DATA SHEET

Date of issue: 18.05.2020 | Update: 22.06.2021 | Version: 2.00

Z-ESD v2

Z-ESD is a material which perfectly fits the needs of the industrial sector, especially the electrical and electronics industries. It is durable, warpage resistant, and provides protection against electrostatic discharge which can be particularly damaging to electronic equipment. This unique property can significantly help to reduce the loss of electronic components and generate savings. Z-ESD allows you to print functional objects, elements and casings containing highly sensitive electronics, and tools used for control processes.



Mechanical Properties	Metric	Imperial	Test Method
Tensile Modulus	2.3 - 2.4 GPa	334 - 348 ksi	DIN 53457
Thermal Properties	Metric	Imperial	Test Method
Glass Transition Temperature	80 - 90° C	176 - 194° F	DSC
Other Properties	Metric	Imperial	Test Method
Specific Gravity	1.31 - 1.38 g/cm ³	10.9 - 11.5 lb/gal	
Surface Resistivity	10 ⁵ - 10 ⁸ Ω/cm ²	6.45*10 ⁵ - 6.45*10 ⁸ Ω/in ²	ASTM D 257 1991
Volume Resistivity	10 ⁵ - 10 ⁷ Ω*cm	0.39*10 ⁵ - 0.39*10 ⁷ Ω*in	IEC 60093

The data presented in this document are intended for information and comparison purposes only. They should not be used for project specifications or its quality evaluation. The material's actual properties depend on the printing process conditions, the design structure and its purpose, test conditions, etc.

Product specifications are subject to change without notice.

Each user is responsible for complying with product safety standards, its intended use as well as the law and waste disposal (and recycling) rules for electrical and electronic equipment. Zortrax does not make any express or implied warranties, including but not limited to implied warranties of merchantability or fitness for a particular purpose.

The Zortrax logo is displayed in a bold, lowercase, sans-serif font.

Zortrax S.A.
Lubelska 34
10-409 Olsztyn, Poland
NIP: 5242756595
REGON: 146496404

Contact
Office: office@zortrax.com
Sales Department: sales@zortrax.com
Support Center: support@zortrax.com